
django-appconf Documentation

Release dev

Jannis Leidel and individual contributors

September 14, 2015

1	Overview	3
2	Installation	5
3	Contents	7
3.1	Usage	7
3.2	Reference	8
3.3	Changelog	9

A helper class for handling configuration defaults of packaged Django apps gracefully.

Note: This app precedes Django’s own `AppConfig` classes that act as “objects [to] store metadata for an application” inside Django’s app loading mechanism. In other words, they solve a related but different use case than `django-appconf` and can’t easily be used as a replacement. The similarity in name is purely coincidental.

Overview

Say you have an app called `myapp` with a few defaults, which you want to refer to in the app's code without repeating yourself all the time. `appconf` provides a simple class to implement those defaults. Simply add something like the following code somewhere in your app files:

```
from appconf import AppConfig

class MyAppConf(AppConf):
    SETTING_1 = "one"
    SETTING_2 = (
        "two",
    )
```

Note: `AppConf` classes depend on being imported during startup of the Django process. Even though there are multiple modules loaded automatically, only the `models` modules (usually the `models.py` file of your app) are guaranteed to be loaded at startup. Therefore it's recommended to put your `AppConf` subclass(es) there, too.

The settings are initialized with the capitalized app label of where the setting is located at. E.g. if your `models.py` with the `AppConf` class is in the `myapp` package, the prefix of the settings will be `MYAPP`.

You can override the default prefix by specifying a `prefix` attribute of an inner `Meta` class:

```
from appconf import AppConfig

class AcmeAppConf(AppConf):
    SETTING_1 = "one"
    SETTING_2 = (
        "two",
    )

    class Meta:
        prefix = 'acme'
```

The `MyAppConf` class will automatically look at Django's global settings to determine if you've overridden it. For example, adding this to your site's `settings.py` would override `SETTING_1` of the above `MyAppConf`:

```
ACME_SETTING_1 = "uno"
```

In case you want to use a different settings object instead of the default `'django.conf.settings'`, set the `holder` attribute of the inner `Meta` class to a dotted import path:

```
from appconf import AppConfig

class MyAppConf(AppConf):
```

```
SETTING_1 = "one"
SETTING_2 = (
    "two",
)

class Meta:
    prefix = 'acme'
    holder = 'acme.conf.settings'
```

If you ship an `AppConf` class with your reusable Django app, it's recommended to put it in a `conf.py` file of your app package and import `django.conf.settings` in it, too:

```
from django.conf import settings
from appconf import AppConf

class MyAppConf(AppConf):
    SETTING_1 = "one"
    SETTING_2 = (
        "two",
    )
```

In the other files of your app you can easily make sure the settings are correctly loaded if you import Django's settings object from that module, e.g. in your app's `views.py`:

```
from django.http import HttpResponse
from myapp.conf import settings

def index(request):
    text = 'Setting 1 is: %s' % settings.MYAPP_SETTING_1
    return HttpResponse(text)
```

Installation

Install django-appconf with your favorite Python package manager, e.g.:

```
pip install django-appconf
```


3.1 Usage

It's strongly recommended to use the usual `from django.conf import settings` in your own code to access the configured settings.

But you can also **OPTIONALLY** use your app's own settings object directly, by instantiating it in place:

```
from myapp.models import MyAppConf

myapp_settings = MyAppConf()

print myapp_settings.SETTING_1
```

Note that accessing the settings that way means they don't have a prefix.

AppConf instances don't automatically work as proxies for the global settings. But you can enable this if you want by setting the `proxy` attribute of the inner `Meta` class to `True`:

```
from appconf import AppConf

class MyAppConf(AppConf):
    SETTING_1 = "one"
    SETTING_2 = (
        "two",
    )

    class Meta:
        proxy = True

myapp_settings = MyAppConf()

if "myapp" in myapp_settings.INSTALLED_APPS:
    print "yay, myapp is installed!"
```

In case you want to override some settings programmatically, you can simply pass the value when instantiating the `AppConf` class:

```
from myapp.models import MyAppConf

myapp_settings = MyAppConf(SETTING_1='something completely different')

if 'different' in myapp_settings.SETTING_1:
    print "yay, I'm different!"
```

3.1.1 Custom configuration

Each of the settings can be individually configured with callbacks. For example, in case a value of a setting depends on other settings or other dependencies. The following example sets one setting to a different value depending on a global setting:

```
from django.conf import settings
from appconf import AppConfig

class MyCustomAppConf(AppConf):
    ENABLED = True

    def configure_enabled(self, value):
        return value and not settings.DEBUG
```

The value of MYAPP_ENABLED will vary depending on the value of the global DEBUG setting.

Each of the app settings can be customized by providing a method `configure_<lower_setting_name>` that takes the default value as defined in the class attributes of the `AppConf` subclass or the override value from the global settings as the only parameter. The method **must return** the value to be use for the setting in question.

After each of the `configure_*` methods has been called, the `AppConf` class will additionally call a main `configure` method, which can be used to do any further custom configuration handling, e.g. if multiple settings depend on each other. For that a `configured_data` dictionary is provided in the setting instance:

```
from django.conf import settings
from appconf import AppConfig

class MyCustomAppConf(AppConf):
    ENABLED = True
    MODE = 'development'

    def configure_enabled(self, value):
        return value and not settings.DEBUG

    def configure(self):
        mode = self.configured_data['MODE']
        enabled = self.configured_data['ENABLED']
        if not enabled and mode != 'development':
            print "WARNING: app not enabled in %s mode!" % mode
        return self.configured_data
```

Note: Don't forget to return the configured data in your custom `configure` method if you edit it.

3.2 Reference

class `appconf.AppConf`

A representation of a template tag. For example:

```
class MyAppConf(AppConf):
    SETTING_1 = "one"
    SETTING_2 = (
        "two",
    )
```

configure_*(value)

Method for each of the app settings for custom configuration which gets the value passed of the class attribute or the appropriate override value of the *holder* settings, e.g.:

```
class MyAppConf(AppConf):
    DEPLOYMENT_MODE = "dev"

    def configure_deployment_mode(self, value):
        if on_production():
            value = "prod"
        return value
```

The method **must return** the value to be use for the setting in question.

class AppConf.Meta

An AppConf takes options via a Meta inner class:

```
class MyAppConf(AppConf):
    SETTING_1 = "one"
    SETTING_2 = (
        "two",
    )

    class Meta:
        proxy = False
        prefix = 'myapp'
        required = ['SETTING_3', 'SETTING_4']
        holder = 'django.conf.settings'
```

prefix

Explicitly choose a prefix for all settings handled by the AppConf class. If not given, the prefix will be the capitalized class module name.

For example, acme would turn into settings like ACME_SETTING_1.

required

A list of settings that must be defined. If any of the specified settings are not defined, ImproperlyConfigured will be raised.

New in version 0.6.

holder

The global settings holder to use when looking for overrides and when setting the configured values.

Defaults to 'django.conf.settings'.

proxy

A boolean, if set to True will enable proxying attribute access to the *holder*.

3.3 Changelog

3.3.1 1.0 (2015-02-15)

Note: This app precedes Django's own `AppConfig` classes that act as "objects [to] store metadata for an application" inside Django's app loading mechanism. In other words, they solve a related but different use case than `django-appconf` and can't easily be used as a replacement. The similarity in name is purely coincidental.

- Dropped support of Python 2.5.

- Added support for Django 1.7 and 1.8.
- Modernized test setup.

3.3.2 0.6 (2013-01-28)

- Added `required` attribute to `Meta` to be able to specify which settings are required to be set.
- Moved to Travis for the tests: <http://travis-ci.org/jezdez/django-appconf>
- Stopped support for Django 1.2.X.
- Introduced support for Python \geq 3.2.

3.3.3 0.5 (2012-02-20)

- Install as a package instead of a module.
- Refactored tests to use `django-jenkins` for `enn.io`'s CI server.

3.3.4 0.4.1 (2011-09-09)

- Fixed minor issue in installation documentation.

3.3.5 0.4 (2011-08-24)

- Renamed `app_label` attribute of the inner `Meta` class to `prefix`. The old form `app_label` will work in the meantime.
- Added `holder` attribute to the inner `Meta` class to be able to specify a custom “global” setting holder. Default: “`django.conf.settings`”
- Added `proxy` attribute to the inner `Meta` class to enable proxying of `AppConf` instances to the settings holder, e.g. the global Django settings.
- Fixed issues with `configured_data` dictionary available in the `configure` method of `AppConf` classes with regard to subclassing.

3.3.6 0.3 (2011-08-23)

- Added tests with 100% coverage.
- Added ability to subclass `Meta` classes.
- Fixed various bugs with subclassing and configuration in subclasses.

3.3.7 0.2.2 (2011-08-22)

- Fixed another issue in the `configure()` API.

3.3.8 0.2.1 (2011-08-22)

- Fixed minor issue in `configure()` API.

3.3.9 0.2 (2011-08-22)

- Added `configure()` API to `AppConf` class which is called after configuring each setting.

3.3.10 0.1 (2011-08-22)

- First public release.

A

AppConf (class in appconf), 8

AppConf.Meta (class in appconf), 9

H

holder (appconf.AppConf.Meta attribute), 9

P

prefix (appconf.AppConf.Meta attribute), 9

proxy (appconf.AppConf.Meta attribute), 9

R

required (appconf.AppConf.Meta attribute), 9